

## Installation Instructions for Triad Deadbolts

### TOOLS REQUIRED FOR REMODELING OR NEW CONSTRUCTION:

- 1 phillips head screwdriver
- 1 2" holesaw
- 1 1" drill
- 1 chisel

### TOOLS REQUIRED FOR REPLACEMENT:

- 1 phillips head screwdriver

FOLLOW STEPS 6,7,8,9,10 FOR DO-IT-YOURSELF REPLACEMENT, FOLLOWING REMOVAL OF EXISTING LOCK.

### REPLACING EXISTING DEADLOCKS:

Before beginning, measure from center of lock to door edge in order to check length of backset on existing lock to that of new lock. The backset length is stated clearly on front of package. If backset size is the same, continue; otherwise, you'll have to replace lock with proper size lock and backset.

### 1. MARK DOOR

A. Fold and apply template to high edge of door bevel and mark center of door edge as indicated on template at the desired height from the floor.


8. Mark center hole on door face through guide on template. For either 2 1/8" or 2 3/4" backset.

### 2. DRILL HOLES

A. Drill thru door face as marked for lockset: It is recommended that holes be drilled from both sides to prevent splitting. Hole size is 2" for standard installations.

B. Drill 1" hole in center of door edge thru to 2" hole for latch

### INSTRUCTION FOR ADJUSTABLE DEADBOLT



#### TO CHANGE 2-3/8" TO 2-3/4"

Thumb press the end of the latch, with the Adjustable Slot facing toward yourself, turn the body of the latch clockwise and make sure that THE PIN DROP INTO THE SECONDARY SLOT, THEN PULL TO THE SIDE. Twist the body of the latch counterclockwise TILL THE PIN DROP INTO THE UPPER PRIMARY SLOT.

60mm (2-3/8")  
70mm (2-3/4")

### 3. INSTALL LATCH

A. Insert latch in hole, keeping it parallel to face of door. Mark outline and remove latch.

B. Chisel 1/8" deep on latch face is flush with door edge.

C. Chisel door to catch latch in upper position in hole as shown in Start Tighten screws.

### 4. INSTALL STRIKE

A. Close door against door stop. Insert edge of template against the flat side of latch bolt, and mark template at edge of door jamb to locate strike opening. Move 3/8" toward door stop to locate center line for screws and 1" hole. This will insure the proper location of the strike.

JAM 13

B. Chisel 1/16" deep for strike matching 1" hole in door Jamb. Insert and tighten screws.

## Name of lock component

